

RUBBER CRUMB

PRODUCT DATA SHEET

Rubber Crumb is a specially formulated rubber based water proofing and insulating coating system that is UV stable, flexible, colour fast, trafficable and designed to be 100% waterproof at full curing.

designed to be 100% waterproof at full curing.
Rubber Crumb is specifically formulated to water proof and insulate flat concrete roof surfaces and substrates. Adhesion Promoted.
Black. Top layer colour choice of 90 Colors as per color chart
Special Colour mixes on request
Confirm integrity of substrate - Sound and non-degrading.
Ensure that the substrate is dry and fee of debris, dust or any objects that might cause non-adhesion.
Rubber Crumb is pre-mixed.
Ensure that the substrate that is to be coated is clean and dry before application.
Continuous application by troweling and brushing is recommended.
Rubber Crumb is applied in a 40 mm layer.
Allow to dry before top layers are applied.
Drying time under normal conditions: 24 hrs.
Rubber Crumb water proofing and Insulation "system" includes the application of 2 coats of DampEnd (cementitious) 2 coats of ThermoSeal and 2 coats of Hydroseal.
20 Liter + 15 kg = 2.5 sq. @ 40 mm
Touch Dry: 1 – 2 Hours at ± 25°C
Full Curing: 7 Days at ± 25°C
Clean water
>90°C
SP 1.1
Low VOC's <1 %
LOW VOC 5 \ 1 /0
Non-Flammable
Non-Flammable
Non-Flammable Water Resistant



RUBBER CRUMB

Safety Precautions & Reactivity:	No specific hazards associated with this product.
Toxicology	
Inhalation:	No specific health warnings noted
Ingestion:	No harmful effect expected in amount likely to be indigested by accident consult a Physician immediately.
Skin Contact:	Prolonged contact may cause dryness of the skin.
Eye Contact:	May cause temporary eye irritation.
Health Warnings:	This product has low toxicity. Only large volumes may have adverse impact on human health.
Ecological Information: Eco Toxicity:	100 % Eco Friendly
Persistence & Degradability:	The product is expected to be biodegradable.
Environmental Hazards:	Non-environmentally hazardous.
Pack size:	20Litre containers and 15 kg packs
Shipping Weight:	22 Kg + 15 kg
Storage:	9 Months maximum at 25°C
	Store in cool dry conditions

DISCLAIMER

This data sheet is issued as a guide for use of the product(s) concerned. Whilst Sealpro endeavors to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot – (as Sealpro has no direct or continuous control over where and how Sealpro products are applied) – accept any liability either directly or indirectly arising from the use of Sealpro products, whether or not in accordance with any advice, specification, recommendation or information given by the company. Where other products are to be used in conjunction with this material, the relevant technical data sheets should be consulted to determine total requirements. Sealpro has a wealth of technical and practical experience built up over years in the company's pursuit of excellence in building and construction technology.

General Disclaimer

The material and information in these sheets are provided as a guide and without warranties of any kind, either expressed or implied. All warranties, including but not limited to, implied warranties by a representative and fitness for a particular purpose, are disclaimed. In no event shall the Company, nor any of its subsidiaries or affiliates, be liable to any party for any cost or damages, including any direct, indirect, special, incidental, or consequential damages, arising out of the incorrect choice of product and/or method of application

Intellectual Property

Except as indicated otherwise, all information, text, graphic images, features or functions contained in these Data sheets are the exclusive property of Sealpro and may not be copied or distributed, in whole or in part, without the Company's express written consent. However, you may download or print any Data Sheets from the website for personal, non-commercial use, provided you do not remove any copyright notices