



HYDRO SEAL

This unique proudly South African product was engineered especially for extreme weather conditions focusing on the shortfalls of existing sealant and coating products.

SealPro's superior waterproofing product allows for affordability, ease of application and guaranteed workmanship.

Hydro Seal is a long-lasting low maintenance waterproofing product with exceptional adhesive properties used for waterproofing of roofs, parapets, patios, hollow-core slabs, retaining walls, foundations, water features, dams etc.

It bonds to existing torch on systems and transforms these jointed surfaces to a seamless membrane. By using a double coat spray-on application we ensure that all possible leaks are covered with a flexible, UV stable and non-flammable plastic-based coating with a 5 year guarantee *(T's & C's apply) and 15 to 20 year life expectancy.

It is available in 90 pre-mixed colours and can be matched to specification in most cases, making Hydro Seal perfect as a final finished coating. This guarantees a saving on valuable material, labour, time and money.

The seamless seal on tiled roofs prevents the movement of tiles and doubles as a security measure for burglar attempts through roofs. Waterproofing of valleys, parapets, box gutters, roof screws, flash-boards and ridging has never been made easier, with just a paint brush and a small roll of membrane water-proofing can be accomplished within a few minutes. There is no need for a third or fourth coat which means much more covering with lesser product and in half the time.

Key Features:	Waterproofing: 5% water up take over 14 days, ponding. Mechanically and Chemically Waterproof. Seamless Coating that can conform to any contour. 98% Eco Friendly. No Primer required. Colour Matching to existing substrate.
Benefits:	Cost saving on preparation, no primer required (material), and labour. No Colour Change. Adheres to any substrate including existing torch on systems. Flexible UV Stable Coating, Highly resistant to acids and chlorine, durable, colourfast and long lasting. Water base, no harmful solvent and or chemicals. Green, environmentally friendly to children, pets and plants.
Surface Preparation:	Prepare substrate to desired finish before applying Hydro-Seal. Ensure that all surrounding areas are covered and masked to avoid damage and over spray. Ensure that the base is dry and free of debris, dust or any objects that might cause non-adhesion to the substrate.
Application & Coverage:	Roll-on: 3 Coat Application, coverage achieved 20-30m ² per 20 ℓ Kit. Airless Spray: 2 Coat Application, coverage achieved 20-30m ² per 20 ℓ Kit.

Contact:: Louw Serfontein, UWES CC, Windhoek, Namibia
Mob: +264 (0)81 781 068; E-mail: uwescc@gmail.co